Issue Date: 25 April 2019 Version No: 1 Revision No: 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name: p-grow

Substance name: Mixed Ashes – Meat and Bone Meal Ash

EC Number: 931-597-4 **CAS Number:** 68131-74-8

REACH Registration Number: 01-2119516041-58-0010

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Use: EU Category SU1: Agriculture, forestry and fishing -

Fertilisers derived mainly from incinerated poultry litter. Classified as compound fertilisers in Groups 2C of Schedule 1: Section A of the UK Fertilisers Regulations

1991.

Uses advised against: None determined

1.3 Details of the supplier of the safety data sheet:

Supplier: Fibrophos Ltd

6 Deben Mill Business Centre

Old Maltings Approach

Woodbridge Suffolk IP12 1BL

Contact numbers: Telephone: +44 (0) 7788 715011

Alternative Telephone: +44 (0) 8450 510510

E-mail contact: kevin.williams@eprl.co.uk

1.4 Emergency telephone number:

Emergency contact: Telephone: +44 (0) 7788 715011 (available 24 hours a

day, 7 days a week)

E-mail: kevin.williams@eprl.co.uk

SECTION 2: Hazards identification

This product is not classified as hazardous, hence classification according to Regulation (EC) No 1272/2008 and its amendments is not applicable. Safety Data Sheets, in accordance with Annex II and Article 32 of Regulation EC 1907/2006, do not have to be provided for non-hazardous products, however this information is provided as a courtesy to our customers in a similar format for ease of use.

2.1 Classification of the substance or mixture

2.1.1 Classification according to according to Regulation (EC) No 1272/2008:

Not classified.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms: None.

Signal word: None. Hazard Statement: None.

Precautionary Statements: None.

Supplemental Hazard information (EU): Not applicable.

2.3 Other hazards: None known.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name	EC Number	CAS Number	% composition by wt
Ashes (residues)	931-597-4	68131-74-8	100 %

The products are prepared by blending ashes produced from the incineration of meat and bone meal.

3.2 Mixtures

Not applicable.

SECTION 4: First aid measures

4.1 Description of first aid measures

Ingestion Wash mouth with water and give copious quantities to drink. Do

not induce vomiting. Obtain medical advice if more than small

quantities have been swallowed.

Skin contact Remove contaminated clothing, brush off any loose particulates and

wash the affected area with soap and running water.

Eye contact Immediately wash out with eye-wash bottle containing saline

solution. Obtain medical advice if symptoms persist.

Inhalation Remove to fresh air. Irrigate nose and throat with water for 20

minutes. Obtain medical advice if symptoms persist.

4.2 Most important symptoms and effects, both acute and delayed

IngestionNo symptoms or effects known.Skin contactNo symptoms or effects known.Eye contactNo symptoms or effects known.InhalationNo symptoms or effects known.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

4.3 Indication of immediate medical attention and special treatment needed

None. The following advice is recommended for facilities handling the substance:

First aid facilities Safety shower, hand and eye washing facilities are recommended

for the workplace.

Medical treatment Show this safety data sheet to medical personnel. Give

symptomatic treatment and supportive therapy.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide, dry chemical, foam, and sand are compatible with the product.

Unsuitable extinguishing media: None Known.

5.2 Specific hazards arising from the substance or mixture

No specific hazards are anticipated with substance. The product is not flammable, explosive or oxidising and is unlikely to decompose to hazardous products if involved in a fire. Dusts may produce a physical explosion hazard, so avoid dust formation.

5.3 Advice for fire fighters

Fire fighters should wear approved self-contained breathing apparatus and full protective clothing as standard.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure full personal protection is worn (see Section 8). Keep unauthorised personnel from the spillage area. Avoid inhalation of dust.

6.2 Environmental precautions

The substance is considered not hazardous to the environment and no special precautions are needed.

6.3 Methods and material for containment and cleaning up

Carefully sweep up and place in suitable container for disposal. Wipe off residual product and then wash contaminated surfaces with water, collect washings for safe disposal. Avoid dust formation. Follow in-house standard procedures for responding to large spills.

6.4 Reference to other sections

For personal protection, see Section 8.

For disposal of waste from clean up operations, see Section 13.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Utilise appropriate industrial hygiene and Local Exhaust Ventilation (LEV), wherever possible. Avoid contact with skin and eyes, and inhalation of dust. Wear protective clothing and dust respirator as detailed in Section 8. Always wash hands after handling.

Avoid formation of dust clouds, and dispose of as detailed in section 6.3 above.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place, away from direct sunlight.

7.3 Specific end use(s)

End uses and associated exposures are addressed in the attached annex. Ensure that Local Exhaust Ventilation is in effect, whenever possible, in order to reduce the concentration of dust in the atmosphere.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Occupational exposure limits:

Substance	Control parameter	Value	Basis
Dust	Limit value – 8 hours	10 mg/m³ (inhalable) 4 mg/m³ (respirable)	UK. EH40 WEL - Workplace Exposure Limits Control of Substances Hazardous to Health Regulations 2002 (as amended).

8.1.2 Biological Limit Values: None established for the product or its components.

8.1.3 PNECs and DNELs:

Derived No Effect Levels (DNELs):

No acute Derived No Effect Level (DNEL) derived due to an absence of effects.

Oral Systemic Derived No Effect Level (DNEL)(Long term): Not determined

Dermal Systemic Derived No Effect Level (DNEL)(Long term): 7 mg/kg/day

Inhalation Systemic Derived No Effect Level (DNEL)(Long term): 1.4 mg/m³

Predicted No EffectConcentrations (PNECs):

PNEC	Assessment factor	Remarks/Justification
PNEC aqua (freshwater): 0.213 mg/L	100	Extrapolation method: assessment factor Data from short-term toxicity tests from three trophic levels- lowest EC50 (EC50 = 21.3 mg/L)
PNEC aqua	1000	Extrapolation method: assessment factor

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

PNEC	Assessment factor	Remarks/Justification
(marine water): 0.0213 mg/L		Data from short-term toxicity tests from three trophic levels- lowest EC50 (EC50 = 21.3 mg/L)
PNEC aqua (intermittent		Extrapolation method: assessment factor
releases): 0.0213 mg/L	100	Data from short-term toxicity tests from three trophic levels- lowest EC50 (EC50 = 21.3 mg/L)
PNEC sediment (freshwater): 4593 mg/kg sediment dw		Extrapolation method: partition coefficient
PNEC sediment (marine water): 459 mg/kg sediment dw		Extrapolation method: partition coefficient
PNEC STP: 1	100	Extrapolation method: assessment factor
mg/L	Activated sludge growth inhibition test (EC50 > 100 mg/L)	
PNECsoil		No data for estimating PNECsoil

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure that Local Exhaust Ventilation is in effect, whenever possible, in order to reduce the concentration of dust in the atmosphere. The rate of air exchange should be a minimum of 15 air changes per hour.

Safety shower, hand and eye washing facilities are recommended for the workplace.

8.2.2 Individual protection measures, such as personal protective equipment

Wherever the substance is available for exposure the following PPE should be utilised:

Powder dust mask: EN149 as minimum standard Gloves: EN374 as minimum standard

Eye protection: EN166 as minimum standard, eye protection should be

safety goggles providing side splash protection.

Protective clothing: EN368 as minimum standard

8.3 Environmental exposure controls

The substance is not classified as hazardous to the environment. No special controls are required for the substance.

For further details see the appended exposure scenario.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Fine grey powder

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Odour Slight odour of residual ammonia

Odour threshold

Melting point/freezing point

>300 °C

Initial boiling point and boiling range

>300 °C

Density Approximately 1000 kg/m³
Vapour pressure No data, but expected to be not

Volatile

Vapour densitiy

Surface tension

No data

No data

Solubility(ies) Water: <1mg/l at 20 °C
Partition coefficient No data available
Flash point No data available
Flammability Non flammable
Auto flammability No self-ignition

Explosive properties Not explosive based on structure and

experience in use.

Oxidising properties Not oxidising

Principally alkaline, up to 12.8
Particle size

Mass Median Diameter: 35.873 μm

Volume weighted mean:90.301 µm

Evaporation rate No data Upper/lower flammability or explosive limits No data

Viscosity Not applicable

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

Exothermic rehydration reaction in contact with water, releases trace amounts of ammonia.

10.2 Chemical stability

Stable under recommended storage and handling conditions.

10.3 Possibility of hazardous reactions

Alkaline in nature (a 10% aqueous extract has a pH up to 11-12.5) and may react with strong acids and can attack aluminium, lead and brass if exposed to moisture.

10.4 Conditions to Avoid

Avoid exposure to strong acids and exposure to metals (e.g. aluminium, lead and brass) in the presence of moisture.

Avoid exposure to ammonium salts such as ammonium nitrate and ammonium sulphate.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.5 Incompatible materials

Ammonium salts such as ammonium nitrate and ammonium sulphate.

10.6 Hazardous decomposition products

Ammonia.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Not classified for

acute toxicity.

Oral: >2000 mg/kg (based on 28-day oral toxicity

data)

Dermal: No data Inhalation: No data

Skin corrosion/irritation: Not classified.

Determined not to be irritating to skin in an in vitro skin irritation: Reconstructed Human

Epidermis Model Test (OECD 439).

Serious eye damage/irritation: Not classified.

No data available.

Respiratory or skin sensitisation: Not classified.

Non-sensitising (based on expert

assessment of metal content analysis)

Mutagenicity: Not classified.

In vitro Ames test (OECD Method 471; Salmonella typhimurium, Escherichia coli)

Non-mutagenic

In vitro chromosome aberration (OECD Method 473; human

lymphocytes)

Non-clastogenic

In vitro mouse lymphoma assay

Not mutagenic

(OECD Method 476; L5178Y cells)

In vivo mutagenicity No data available

Carcinogenicity: Not classified.

No data available. Anticipated to represent no hazard based on mutagenicity and

experience of use.

Reproductive toxicity: Not classified.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

No data available. Anticipated to represent no hazard based on mutagenicity and repeated dose non human toxicity data.

STOT-single exposure: Not classified.

No specific data available. Considered likely to cause a hazard of respiratory irritation based on known irritation/

corrosivity potential and high pH.

STOT-repeated exposure: Not classified.

NOAEL (oral, 28 d, rat) 500 mg/kg/day; Not classified as Harmful. No serious toxic effects and no target organs could be

defined.

Aspiration hazard: Not classified.

No hazard anticipated. Substance is not a

low viscosity inorganic substance.

11.2 Other information: No other information available.

SECTION 12: Ecological information

12.1 Toxicity Not classfied.

Fish: LC₅₀ (96 h; fish; OECD Method 203): Inadequate

data

Daphnia magna: NOEC 3.2 mg/L based on reproduction study. Algal growth inhibition: EC_{50} (72 h; algae; OECD Method 201): 21.3 mg/L

Activated sludge

Respiration Inhibition: NOEC (3 h): 100 mg/L test material (nominal)

12.2 Persistence and degradability

As the registered substance is an inorganic mixed ash with various trace metal oxides it was not technically possible, or necessary to perform testing on persistence.

Hydrolysis Not determined due to physical nature. No mode of

hydrolysis for inorganic substance.

Biodegradation Not determined due to physical nature. No mode of

biodegradation for an inorganic substance.

12.3 Bioaccumulative potential

LogBCF ≤ 107. Mixed ashes is considered to be not bioaccumulative.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Ash does not fulfill the criteria of PBT or vPvB and therefore does not require classification as PBT compound.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Criterion	Method	Result of the test	Ash
Р	Not applicable	Not biodegradable	Р
В	BCFs from literature	LogBCF ≤ 107	Not B
Т	Daphnia magna reproduction test (OECD No 211)	NOEC 3.2 mg/l	Not T

12.6 Other adverse effects

None known at the time of issuance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

All disposals must be in accordance with current EU, national and/or local regulations.

SECTION 14: Transport information

Not classified as hazardous for transport.

14.1 *UN number*: Not applicable

14.2 UN proper shipping name: Not applicable

14.3 Transport hazard class: Not applicable14.4 Packing group: Not applicable

14.5 Environmental Hazards: Not applicable

14.6 Special Precautions for user: Not applicable

14.7 Transport in bulk according to

Annex II of Marpol 73/78 and the IBC Code: Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation of the European Parliament and Council Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Compliant

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) and its adaptations: Compliant

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors: Neither banned nor restricted

Restrictions on the marketing and use of certain dangerous substances and preparations:

Neither banned nor restricted

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII):Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Neither banned nor restricted

Candidate List of Substances of Very High Concern for Authorisation: Neither banned nor restricted

REACH - List of substances subject to Authorisation (Annex XIV) : Not applicable Regulation (EC) No 1005/2009 on substances that deplete the ozone layer: Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances: Not applicable

UK regulations

The Control of Substances Hazardous to Health Regulations 2002 (as amended). : Compliant

EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended). Health and Safety Executive, Second edition, published 2011.

Control of Asbestos Regulations 2012 (SI 2012/632).

The Control of Lead at Work Regulations 2002 (CLAW).

The Control of Major Accident Hazards (COMAH) Regulations.

The Dangerous Substances and Explosive Atmospheres Regulations (DSEARs) 2002 (SI 2002/2776).

15.2 Chemical Safety Assessment

A full Chemical safety Assessment and Chemical Safety Report has been conducted on this substance by the Ash Consortium. Suitable exposure scenarios, relevent to the recommended use(s) are appended to this Safety Data Sheet. The Chemical Safety Report is an industry standard document and uses full industry details that are not specific to Fibrophos Limited. Any appendices from the Chemical Safety Report are not attached to this Safety Data Sheet. Please contact the supplier should any additional information from the Chemical Safety Report be required.

SECTION 16: Other information

Full text of H-statements referred to under Sections 2 and 3:

Not applicable.

Revisions: Update to SDS format, particularly Section 2.

Date of revision: 25 April 2019

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Methods of evaluation:

Classification and labeling has been determined according to EU Regulation No 1272/2008 (including amendments) and take into account the intended product use.

References

Proprietary test data, including data available from the Ash Consortium lead registration dossier.

EU Directive 1907/2006 (REACH).

EU Directives 67/548/EEC (including amendments)

Regulation (EC) No 1272/2008 (including amendments)

Annex VI of Regulation 1272/2008 on Harmonised Classification and Labeling for Certain Hazardous Substances.

Personal protective equipment (PPE): 89/686/EEC. European occupational exposure limits: 2000/39/EC.

Protection of health and safety of workers: 98/24/EC.

RTECS (Registry of Toxic Effects of Chemical Substances), 2004.

Abbreviations

BCF: Bioconcentration Factor.

DNEL: Derived No Effect Level

EC50: half maximal effective concentration

LD50: lethal dose, 50%

NOEC, No Observed Effect Concentration PBT: Persistent, bioaccumulative and toxic PNEC: Predicted No Effect Concentration.

PPE: Personal protective equipement. STOT: Specific target organ toxicity

STP: Sewage treatment plant.

vPvB: Very persistent and very bioaccumulative.

Other information:

The information contained herein is carefully presented, based on the data available. However, all precautions described herein are for normal handling, not for special handling. Please establish the safe usage in accordance with your handling procedures by reference to this SDS and applicable laws and guidance. In addition, the description, composition, and physical/chemical properties are typical values and not guaranteed for this product.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Appendix 1: Relevant Exposure Scenarios taken from the Chemical Safety Report for

this substance

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

9.1. Production of Ash

Ash is by-product from gasification and combustion of carbonaceous materials, like biomass, biofuels, peat and sludge with coal, solid recovered fuel (SRF) and supplementary fuels as needed. The following elements may be present as oxides: aluminium, calcium, iron, magnesium, phosphorous, potassium, sodium and silicon. The combustion technologies could be grid firing, fluidized bed (bubbling or circulated) firing or pulverized firing. The burning temperature is typically above 800°C.

This use covers production in closed process with or without a dedicated sampling point. Ash is transferred as bulk material in open or closed systems.

The production itself occurs in a closed system. Typically, ash is collected and transferred in closed or partially closed systems with or without a dedicated sampling point. Ash is stored indoors or outdoors typically e.g. in silos or as open bulk material. Contact with ash is occasional and mainly in maintenance. Minor amounts of ash may end up directly or indirectly to waterways via drainage.

9.1.1. Exposure scenario

Section 1	Exposure Scenario Title
Title	Production of Ash
	Sector of Use: Industrial (SU6b, SU8, SU23)
Use Descriptor	Process Categories: PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, PROC19
	Environmental Release Categories: ERC 1
Processes, tasks, activities covered	Burning of combination of carbonaceous materials in closed process with or without sampling, bulk transfers, maintenance, associated laboratory activities and storage.
Section 2	Operational conditions and risk management measures
Section 2.1	Control of worker exposure
Product characteristics	
Physical form of product	Solid, not explosive or flammable, particle size distribution 0.2 - 2000 µm. Irritates skin and eyes.
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13]
Amounts used	Not applicable
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]
Human factors not influenced by risk management	Not applicable

	Assumes activities are at ambient temperature (unless stated differently) [G17]
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]
	Solid, high dustiness [OC6]
Contributing Scenarios	Risk Management Measures
General exposures (closed systems) [CS15]. Boiler	Handle substance within a closed system [E47]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7].
General exposures (closed systems) [CS15]. Temporary storage silo	Handle substance within a closed system [E47]. Ensure material transfers are under containment or extract ventilation [E66]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7].
Process sampling [CS2] Non-dedicated facility [CS81]	Wear suitable gloves (tested to EN374) and eye protection [PPE19]. Avoid carrying out operation for more than 1 hour [OC11]. If this time is exceeded or dust is formed, wear a respirator conforming to EN140 with Type P1 filter or better. Outdoor [OC9].
Process sampling [CS2] Dedicated facility [CS82]	Wear suitable gloves (tested to EN374) and eye protection [PPE19]. Avoid carrying out operation for more than 1 hour [OC11]. If this time is exceeded or dust is formed, wear a respirator conforming to EN140 with Type P1 filter or better.
Laboratory activities [CS36].	Handle in a fume cupboard or under extract ventilation [E83]. Wear suitable gloves tested to EN374 [PPE15].
Bulk transfers [CS14] Use in contained systems [CS38].	Transfer via enclosed lines [E52].
Bulk transfers [CS14] (open systems) [CS108]	Wear suitable gloves tested to EN374 [PPE15]. Avoid carrying out operation for more than 1 hour [OC11]. If this time is exceeded or dust is formed, wear a respirator conforming to EN140 with Type P1 filter or better.
Equipment cleaning and maintenance [CS39] Cleaning of solids filtering equipment [CS120]	Wear suitable gloves (tested to EN374), coverall and eye protection [PPE23]. Wear a respirator conforming to EN140 with Type P1 filter or better.
Mixing operations (open systems) [CS30]	Wear suitable gloves (tested to EN374) and eye protection [PPE19]. Avoid carrying out operation for more than 1 hour [OC11]. If above technical/organisational control measures are not feasible, then adopt following PPE [PPE30]: Wear a respirator conforming to EN140 with Type P1 filter or better.

Bulk product storage [CS85] (closed systems) [CS107]	Store substance within a closed system [E84].
Bulk product storage [CS85] (open systems) [CS108]	Wear suitable gloves tested to EN374 [PPE15].
Section 2.2	Control of environmental exposure
Assessment method	EUSES
Product characteristics	Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment.
	EU production: 34100 ktonnes per year
Amounts used	Regional production: 34100 ktonnes per year
	Site production: 300 ktonnes per year
Frequency and duration of use	Emission days per year: 300
Environmental factors not influenced by risk management	Local freshwater dilution fraction: 10
	Local marine dilution fraction: 100
	Release fraction to air from process: 1.0E10-5
Other Operational Conditions of use affecting environmental exposure	Release fraction to (waste)water from process: 3.0E10-3
	Release fraction to soil from process (regional): 0.0001 (ERC)
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Air emission controls to be added.
Organisation measures to prevent/limit release from site	Dispose of waste in accordance with environmental legislation.
Conditions and measures related to municipal sewage treatment plant	Not applicable
Conditions and measures related to external treatment of waste for disposal	Not applicable
Conditions and measures related to external recovery of waste	Not applicable

Other environmental control measures additional to above	Do not discharge directly in waterways.
Section 3	Exposure Estimation
3.1. Health	When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1 as indicated in Appendix A.1.
3.2. Environment	When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterisation ratios are expected to be less than 1.
Section 4	Guidance to check compliance with the Exposure Scenario
4.1. Health	Confirm that RMMs and OCs are as described or of equivalent efficiency. See Appendix A.1 for details of efficiencies and OC.
4.2. Environment	Confirm that RMMs and OCs are as described or of equivalent efficiency. The required efficiency removal from water is 92.5% which would be typically found in waste-water treatment plant.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

9.3. Formulation and repacking of Ash

Includes uses corresponding to formulation and granulation. Material can be stored in closed containers or as bulk material indoors or outdoors. Use includes sampling, laboratory analysis and occasional intimate contact with the material, e.g. hand-mixing. Some ash can enter soil and waterways.

9.3.1. Exposure scenario

Section 1	Exposure Scenario Title
Title	Formulation and repacking of Ash
	Sector of Use: Industrial and professional (SU10, SU13)
Use Descriptor	Process Categories:PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15, PROC19
	Product Categories: PC0 (Building and construction materials), PC9b, PC12
	Environmental Release Categories: ERC 2
Processes, tasks, activities covered	Formulation and granulation of Ash and its mixtures and its mixtures in continuous or batch processes, including repacking, material transfers, storage and associated laboratory activities.
Section 2.1	Control of worker exposure
Product characteristics	
Physical form of product	Solid, not explosive or flammable, particle size distribution 0.2 - 2000 µm. Irritates skin and eyes.
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13]
Amounts used	Not applicable
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]
Human factors not influenced by risk management	Not applicable
Other Operational Conditions	Assumes activities are at ambient temperature (unless stated differently) [G17]
affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]
Risk Management Measures	
Mixing operations (closed systems) [CS29] Closed batch process	Formulate in enclosed or ventilated mixing vessels [E46].
Mixing operations (open systems) [CS30] Batch process	Formulate in enclosed or ventilated mixing vessels [E46].

d or ventilated miving
d or ventilated mixing
(tested to EN374) and eye Avoid carrying out operation [OC11]. If this time is ormed, wear a respirator with Type P1 filter or better.
(tested to EN374) and eye Avoid carrying out operation [OC11]. If this time is ormed, wear a respirator with Type P1 filter or better.
(tested to EN374) and eye Avoid carrying out operation [OC11]. If this time is ormed, wear a respirator with Type P1 filter or better.
board or under extract ar suitable gloves tested to
OC1]: No specific measures or suitable gloves tested to list is formed, wear a to EN140 with Type P1 filter
[OC6]: Transfer via
OC1]: Ensure material ontainment or extract
(tested to EN374) and eye Vear a respirator conforming P1filter or better [PPE29].
in a closed system [E84].
tested to EN374 [PPE15].
nental exposure
ninerals, oxides and soluble r solubility of ash is estituents of Ash may e in a long run under ntal conditions. Hazardous to
30 ktonnes per year

	D : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 :
	Regional production: 10230 ktonnes per year
	Site production: ktonnes per year
	Fraction of main source: 0.6
Frequency and duration of use	Emission days per year: 300
Environmental factors not influenced	Local freshwater dilution fraction: 10
by risk management	Local marine dilution fraction: 100
	Release fraction to air from process: 2.5E10-3
Other Operational Conditions of use affecting environmental exposure	Release fraction to surfacewater from process: 1.0E10-3
	Release fraction to soil from process (regional): 0.0001 (ERC)
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	Air emission controls to be added.
Organisation measures to	Dispose of waste in accordance with
prevent/limit release from site	environmental legislation.
Conditions and measures related to municipal sewage treatment plant	Not applicable
Conditions and measures related to external treatment of waste for disposal	Not applicable
Conditions and measures related to external recovery of waste	Not applicable
Other environmental control measures additional to above	Do not discharge directly in waterways.
Section 3	Exposure Estimation
3.1. Health	When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1 as indicated in Appendix A.3.
3.2. Environment	When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterisation ratios are expected to be
	less than 1.

Section 4	Guidance to check compliance with the Exposure Scenario	
4.1. Health	Confirm that RMMs and OCs are as described of equivalent efficiency. See Appendix A.3 for details of efficiencies and OC.	
4.2. Environment	Confirm that RMMs and OCs are as described or of equivalent efficiency. The required efficiency removal from water is 92.5% which would be typically found in waste-water treatment plant.	

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

9.2. Distribution of Ash

Loading/unloading of Ash with dedicated or non-dedicated systems. Direct short-time contact with ash is typical. Some Ash ends up to waterways and to soil.

9.2.1. Exposure scenario

Section 1	Exposure Scenario Title			
Title	Distribution of Ash			
	Sector of Use: Industrial and professional (SU6b, SU8, SU23)			
Use Descriptor	Process Categories: PROC2, PROC4, PROC8a, PROC8b, PROC15, PROC19			
	Environmental Release Categories: ERC 1			
Processes, tasks, activities covered	Loading/unloading of Ash, including its distribution and storage.			
Section 2	Operational conditions and risk management measures			
Ocation 0.4	Operational of considerations are a series			
Section 2.1	Control of worker exposure			
Product characteristics				
Physical form of product	Solid, not explosive or flammable, particle size distribution 0.2 - 2000 µm. Irritates skin and eyes.			
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13]			
Amounts used	Not applicable			
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]			
Human factors not influenced by risk management	Not applicable			
	Assumes activities are at ambient temperature (unless stated differently) [G17]			
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]			
	Solid, high dustiness [OC6]			
Risk Management Measures				
Process sampling [CS2] Non- dedicated facility [CS81]	Wear suitable gloves (tested to EN374) and eye protection [PPE19]. Avoid carrying out operation for more than 1 hour [OC11]. If this time is exceeded or dust is formed, wear a respirator conforming to EN140 with Type P1 filter or bette Outdoor [OC9].			
Laboratory activities [CS36]	Handle in a fume cupboard or under extract ventilation [E83]. Wear suitable gloves tested to			

	EN374 [PPE15].	
Bulk transfers [CS14] (closed systems) [CS107]	Transfer via enclosed lines [E52].	
Bulk transfers [CS14] (open systems) [CS108]	Wear suitable gloves tested to EN374 [PPE15]. Avoid carrying out operation for more than 1 hour [OC11]. If this time is exceeded or dust is formed, wear a respirator conforming to EN140 with Type P1 filter or better.	
Equipment cleaning and maintenance [CS39]	Wear suitable gloves (tested to EN374) and eye protection [PPE19]. Wear a respirator conforming to EN140 with Type P1 filter or better.	
Mixing operations (open systems) [CS30]	Wear suitable gloves (tested to EN374) and eye protection [PPE19]. Avoid carrying out operation for more than 1 hour [OC11]. If above technical/organisational control measures are not feasible, then adopt following PPE [PPE30]: Wear a respirator conforming to EN140 with Type P1 filter or better.	
Storage [CS67] (closed systems) [CS107]	Store substance within a closed system [E84].	
Storage [CS67] (open systems) [CS108]	Wear suitable gloves tested to EN374 [PPE15].	
Section 2.2	Control of anvironmental expecure	
Section 2.2	Control of environmental exposure	
Assessment method	EUSES	
	·	
Assessment method	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to	
Assessment method	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment.	
Assessment method Product characteristics	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year	
Assessment method Product characteristics	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year Regional production: 34100 ktonnes per year	
Assessment method Product characteristics Amounts used Frequency and duration of use Environmental factors not influenced	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year Regional production: 34100 ktonnes per year Site production: 300 ktonnes per year	
Assessment method Product characteristics Amounts used Frequency and duration of use	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year Regional production: 34100 ktonnes per year Site production: 300 ktonnes per year Emission days per year: 300	
Assessment method Product characteristics Amounts used Frequency and duration of use Environmental factors not influenced	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year Regional production: 34100 ktonnes per year Site production: 300 ktonnes per year Emission days per year: 300 Local freshwater dilution fraction: 10	
Assessment method Product characteristics Amounts used Frequency and duration of use Environmental factors not influenced by risk management Other Operational Conditions of use	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year Regional production: 34100 ktonnes per year Site production: 300 ktonnes per year Emission days per year: 300 Local freshwater dilution fraction: 10 Local marine dilution fraction: 100	
Assessment method Product characteristics Amounts used Frequency and duration of use Environmental factors not influenced by risk management	EUSES Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment. EU production: 34100 ktonnes per year Regional production: 34100 ktonnes per year Site production: 300 ktonnes per year Emission days per year: 300 Local freshwater dilution fraction: 10 Local marine dilution fraction: 100 Release fraction to air from process: 1.0E10-5 Release fraction to (waste)water from process:	

Dispose of waste in accordance with environmental legislation.
Not applicable
Not applicable
Not applicable
Do not discharge directly in waterways.
Exposure Estimation
When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1 as indicated in Appendix A.2.
When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterisation ratios are expected to be less than 1.
Guidance to check compliance with the Exposure Scenario
Confirm that RMMs and OCs are as described or of equivalent efficiency. See Appendix A.2 for details of efficiencies and OC.
Confirm that RMMs and OCs are as described or of equivalent efficiency. The required efficiency removal from water is 92.5% which would be typically found in waste-water treatment plant.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

9.7. Use of Ash as fertilizer

Wide dispersive professional use of substance and its mixtures.

9.7.1. Exposure scenario

9.7.1. Exposure scenario Section 1 Exposure Scenario Title				
	Exposure Scenario Title			
Title	Use of Ash as fertilizer			
	Sector of Use: Professional (SU1)			
Use Descriptor	Process Categories: PROC1, PROC8a, PROC8b, PROC11			
	Product Categories: PC12			
	Environmental Release Categories: ERC 8E			
Processes, tasks, activities covered	Spreading of Ash as such or as formulation with a dedicated equipment including repackaging, material transfers and storage.			
Section 2	Operational conditions and risk management measures			
Section 2.1	Control of worker exposure			
Product characteristics				
Physical form of product	Solid, not explosive or flammable, particle size distribution 0.2 - 2000 µm. Irritates skin and eyes.			
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13]			
Amounts used	Not applicable			
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]			
Human factors not influenced by risk management	Not applicable			
	Assumes activities are at ambient temperature (unless stated differently) [G17]			
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]			
	Solid, low dustiness [OC1]			
Risk Management Measures				
Bulk transfers [CS14]	No specific measures identified [EI18]. Outdoor [OC9]. If in contact with material, wear suitable gloves tested to EN374.			
Spraying/fogging by machine application [CS25]	If in contact with material, wear suitable gloves tested to EN374. Outdoor [OC9].			

Equipment elegating and			
Equipment cleaning and maintenance [CS39]	Wear suitable gloves tested to EN374 [PPE15].		
Vessel / container cleaning [CS103]	Wear suitable gloves tested to EN374 [PPE15].		
Storage [CS67]	Store finished products in closed containers (e.g bulk tanks, drums, cans) [A5].		
Section 2.2	Control of environmental exposure		
Assessment method	EUSES		
Product characteristics	Ash is composed of minerals, oxides and soluble salts of metals. Water solubility of ash is negligible but the constituents of Ash may become water soluble in a long run under changing environmental conditions. Hazardous to aquatic environment.		
	EU tonnage: 10230 ktonnes per year		
Amounts used	Regional tonnage: 10230 ktonnes per year		
	Fraction of main source:		
Frequency and duration of use	Intermittent release? Emission days per year:		
	Local freshwater dilution fraction: 10		
Environmental factors not influenced by risk management	Local marine dilution fraction: 100		
	Release fraction to air from process (regional): 0.011		
Other Operational Conditions of use affecting environmental exposure	Release fraction to freshwater from process: 0.05		
	Release fraction to soil from process (regional): 0.01 (ERC)		
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil			
Organisation measures to prevent/limit release from site	Dispose of waste in accordance with environmental legislation.		
Conditions and measures related to municipal sewage treatment plant	Not applicable		
Conditions and measures related to external treatment of waste for disposal	Not applicable		
Conditions and measures related to external recovery of waste	Not applicable		

Other environmental control measures additional to above	Do not discharge directly in waterways.	
Section 3	Exposure Estimation	
3.1. Health	When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1 as indicated in Appendix A.9.	
3.2. Environment	When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposures are not expected to exceed the predicted PNECs and the resulting risk characterisation ratios are expected to be less than 1.	
Section 4	Guidance to check compliance with the Exposure Scenario	
4.1. Health	Confirm that RMMs and OCs are as described or of equivalent efficiency. See Appendix A.9 for details of efficiencies and OC.	
4.2. Environment	Confirm that RMMs and OCs are as described or of equivalent efficiency. The required efficiency removal from water is 92.5% which would be typically found in waste-water treatment plant.	

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Appendix 2: Risk Characterisation

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.1. Production of Ash

10.1.1. Human health

10.1.1.1. Workers

Table 42. Substance specific RCRs

Contributing Scenarios	RCR (inhalation)	RCR (dermal)	RCR (all routes)
General exposures (closed systems) [CS15]	0.0100	0.0200	0.0300
General exposures (closed systems) [CS15]	0.0100	0.0043	0.0143
Process sampling [CS2] Non- dedicated facility [CS81]	0.7000	0.0004	0.7004
Process sampling [CS2] Dedicated facility [CS82]	0.5000	0.0196	0.5196
Laboratory activities [CS36]	0.0500	0.0043	0.0543
Bulk transfers [CS14] Use in contained systems [CS38]	0.0000	0.0986	0.0986
Bulk transfers [CS14] (open systems) [CS108]	0.0000	0.0200	0.0200
Equipment cleaning and maintenance [CS39] Cleaning of solids filtering equipment [CS120]	0.5000	0.1959	0.6959
Mixing operations (open systems) [CS30]	0.3500	0.0404	0.3904
Bulk product storage [CS85] (closed systems) [CS107]	0.0100	0.0200	0.0300
Bulk product storage [CS85] (open systems) [CS108]	0.0070	0.0020	0.0090

10.1.1.2. Consumers

Not relevant.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.1.1.3. Indirect exposure of humans via the environment

Table 43. Indirect exposure of humans via the environment

Compartment	Daily dose (local)	DNE L	Daily dose/DNE L
Daily dose through intake of drinking water (mg/kg/d)	2.09E-03	7	2.99E-04
Daily dose through intake of fish (mg/kg/d)	1.7E-04	7	2.43E-05
Daily dose through intake of leaf crops (mg/kg/d)	0.0199	7	2.84E-03
Daily dose through intake of root crops (mg/kg/d)	8.81E-05	7	1.26E-05
Daily dose through intake of meat (mg/kg/d)	2.68E-06	7	3.83E-07
Daily dose through intake of milk (mg/kg/d)	4.99E-05	7	7.13E-06
Daily dose through intake of air (mg/kg/d)	7.6E-03	7	1.09E-03

10.1.2. Environment

10.1.2.1. Aquatic compartment (incl. sediment)

Table 44. Local PECs of aquatic compartment including sediment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Freshwater, dissolved (mg/l)	0.0795	0.213	0.3732
Marine water, dissolved (mg/l)	0.0106	0.0213	0.4977
Freshwater sediment (mg/kg wwt)	1.73E+03	4593	0.3767
Marine water sediment (mg/kg wwt)	231	459	0.5033

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.1.2.2. Terrestrial compartment

Table 45. Local PECs of terrestrial compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Agricultural soil (total) - 30 days (mg/kg wwt)	1.5E+03	18762	0.0799
Agricultural soil (groundwater) (mg/kg wwt)	0.017	not quantifiable	not quantifiable

10.1.2.3. Atmospheric compartment

Table 46. Local PECs of atmospheric compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Air (annual average) (mg/m3)	0.0266	not quantifiable	not quantifiable

10.1.2.4. Microbiological activity in sewage treatment systems

Table 47. Regional PECs of sewage treatment systems

Compartment	Regional PEC	PNEC	PEC/PNEC (RCR)
Sewage treatment plant (mg/l)		1	

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.3. Formulation and repacking of Ash

10.3.1. Human health

10.3.1.1. Workers

Table 53. Substance specific RCRs

Contributing Scenarios	RCR (inhalation)	RCR (dermal)	RCR (all routes)
Mixing operations (closed systems) [CS29]	0.0100	0.0043	0.0143
Mixing operations (open systems) [CS30]	0.0050	0.0986	0.1036
Mixing operations (open systems) [CS30]	0.0050	0.0100	0.0150
Mixing operations (open systems) [CS30]	0.0100	0.4041	0.4141
Process sampling [CS2] Non- dedicated facility [CS81]	0.0500	0.1959	0.2459
Process sampling [CS2] Dedicated facility [CS82]	0.0100	0.0980	0.1080
Laboratory activities [CS36]	0.0500	0.0043	0.0543
Drum and small package filling [CS6] Small scale weighing [CS90]	0.0010	0.0986	0.0996
Bulk transfers [CS14] (closed systems) [CS107] Bulk weighing [CS91]	0.0005	0.0986	0.0991
Bulk transfers [CS14] (closed systems) [CS107] Bulk weighing [CS91]	0.5000	0.0200	0.5200
Equipment cleaning and maintenance [CS39]	0.5000	0.1959	0.6959
Storage [CS67] (closed systems) [CS107]	0.0100	0.0200	0.0300
Storage [CS67] (open systems) [CS108]	0.0350	0.0099	0.0449

10.3.1.2. Consumers

Not relevant.

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.3.1.3. Indirect exposure of humans via the environment

Table 54. Indirect exposure of humans via the environment

Compartment	Daily dose (local)	DNE L	Daily dose/DNE L
Daily dose through intake of drinking water (mg/kg/d)	1.27E-03	7	1.81E-04
Daily dose through intake of fish (mg/kg/d)	1.03E-04	7	1.47E-05
Daily dose through intake of leaf crops (mg/kg/d)	2.24E-03	7	3.2E-04
Daily dose through intake of root crops (mg/kg/d)	8.81E-05	7	1.26E-05
Daily dose through intake of meat (mg/kg/d)	2.42E-06	7	3.46E-07
Daily dose through intake of milk (mg/kg/d)	9.82E-03	7	1.40E-03
Daily dose through intake of air (mg/kg/d)	0.185	7	0.026

10.3.2. Environment

10.3.2.1. Aquatic compartment (incl. sediment)

Table 55. Local PECs of aquatic compartment including sediment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Freshwater, dissolved (mg/l)	0.0445	0.213	0.2089
Marine water, dissolved (mg/l)	7.11E-03	0.0213	0.3338
Freshwater sediment (mg/kg wwt)	967	4593	0.2105
Marine water sediment (mg/kg wwt)	155	459	0.3377

10.3.2.2. Terrestrial compartment

Table 56. Local PECs of terrestrial compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Agricultural soil (total) - 30	1.5E+03	18762	0.0799

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
days (mg/kg wwt)			
Agricultural soil (groundwater) (mg/kg wwt)	0.017	not quantifiable	not quantifiable

10.3.2.3. Atmospheric compartment

Table 57. Local PECs of atmospheric compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Air (annual average) (mg/m3)	2.98E-03	not quantifiable	not quantifiable

10.3.2.4. Microbiological activity in sewage treatment systems

Table 58. Regional PECs of sewage treatment systems

Compartment	Regional PEC	PNEC	PEC/PNEC (RCR)
Sewage treatment plant (mg/l)	[not relevant]	1	[not relevant]

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.2. Distribution of Ash

10.2.1. Human health

10.2.1.1. Workers

Table 48. Substance specific RCRs

Contributing Scenarios	RCR (inhalation)	RCR (dermal)	RCR (all routes)
Process sampling [CS2] Non- dedicated facility [CS81]	0.7000	0.0004	0.7004
Process sampling [CS2] Dedicated facility [CS82]	0.5000	0.0196	0.5196
Laboratory activities [CS36]	0.0500	0.0043	0.0543
Bulk transfers [CS14] (closed systems) [CS107]	0.0875	0.0986	0.1861
Bulk transfers [CS14] (open systems) [CS108]	0.7000	0.0020	0.7020
Equipment cleaning and maintenance [CS39]	0.5000	0.1959	0.6959
Mixing operations (open systems) [CS30]	0.1500	0.4041	0.5541
Storage [CS67] (closed systems) [CS107]	0.0100	0.0200	0.0300
Storage [CS67] (open systems) [CS108]	0.3500	0.0020	0.3520

10.2.1.2. Consumers

Not relevant.

10.2.2. Environment

10.2.2.1. Aquatic compartment (incl. sediment)

Table 49. Local PECs of aquatic compartment including sediment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Freshwater, dissolved (mg/l)		0.213	
Marine water, dissolved (mg/l)		0.0213	
Freshwater sediment		4593	

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
(mg/kg wwt)			
Marine water sediment (mg/kg wwt)		459	

10.2.2.2. Terrestrial compartment

Table 50. Local PECs of terrestrial compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Agricultural soil (total) - 30 days (mg/kg wwt)		18762	
Agricultural soil (groundwater) (mg/kg wwt)		not quantifiable	not quantifiable

10.2.2.3. Atmospheric compartment

Table 51. Local PECs of atmospheric compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Air (annual average) (mg/m3)		not quantifiable	not quantifiable

10.2.2.4. Microbiological activity in sewage treatment systems

Table 52. Regional PECs of sewage treatment systems

Compartment	Regional PEC	PNEC	PEC/PNEC (RCR)
Sewage treatment plant (mg/l)		1	

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.7. Use of Ash as fertilizer

10.7.1. Human health

10.7.1.1. Workers

Table 77. Substance specific RCRs

Contributing Scenarios	RCR (inhalation)	RCR (dermal)	RCR (all routes)
Bulk transfers [CS14]	0.0350	0.0986	0.1336
Spraying/fogging by machine application [CS25]	0.0700	0.0306	0.1006
Equipment cleaning and maintenance [CS39]	0.0500	0.1959	0.2459
Vessel / container cleaning [CS103]	0.0500	0.1959	0.2459
Storage [CS67]	0.0002	0.0043	0.0045

10.7.1.2. Consumers

Not relevant.

10.7.1.3. Indirect exposure of humans via the environment

Table 78. Indirect exposure of humans via the environment

Compartment	Daily dose (local)	DNE L	Daily dose/DNE L
Daily dose through intake of drinking water (mg/kg/d)	1.27E-03	7	1.81E-04
Daily dose through intake of fish (mg/kg/d)	1.03E-04	7	1.47E-05
Daily dose through intake of leaf crops (mg/kg/d)	25.2	7	3.6
Daily dose through intake of root crops (mg/kg/d)	1.21E-04	7	1.73E-05
Daily dose through intake of meat (mg/kg/d)	3.57E-04	7	5.1E-05
Daily dose through intake of milk (mg/kg/d)	6.66E-03	7	9.51E-04
Daily dose through intake of air (mg/kg/d)	9.6	7	1.371

Issue Date: 25 April 2019 Version No: 1 Revision No: 5

10.7.2. Environment

10.7.2.1. Aquatic compartment (incl. sediment)

Table 79. Local PECs of aquatic compartment including sediment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Freshwater, dissolved (mg/l)	0.0445	0.213	0.2089
Marine water, dissolved (mg/l)	7.11E-03	0.0213	0.3338
Freshwater sediment (mg/kg wwt)	967	4593	0.2105
Marine water sediment (mg/kg wwt)	155	459	0.3376

10.7.2.2. Terrestrial compartment

Table 80. Local PECs of terrestrial compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Agricultural soil (total) - 30 days (mg/kg wwt)	2.05E+03	18762	0.1093
Agricultural soil (groundwater) (mg/kg wwt)	0.0234	not quantifiable	not quantifiable

10.7.2.3. Atmospheric compartment

Table 81. Local PECs of atmospheric compartment

Compartment	Local PEC	PNEC	PEC/PNEC (RCR)
Air (annual average) (mg/m3)	33.6	not quantifiable	not quantifiable

10.7.2.4. Microbiological activity in sewage treatment systems

Table 82. Regional PECs of sewage treatment systems

Compartment	Regional PEC	PNEC	PEC/PNEC (RCR)
Sewage treatment plant (mg/l)	[not relevant]	1	[not relevant]